

STATEMENTS

LAWRENCE WEINER

1968

Certain Specific Statements are
reproduced by kind permission of
the people who own them

General Statements

A field cratered by structured simultaneous TNT explosions

A removal of an amount of earth from
the ground

The intrusion into this hole of a st
andard processed material

One sheet of plywood secured to the
floor or wall

One regular rectangular object placed across an international boundary allowed to rest then turned to and turned upon to intrude the portion of one country into the other

A removal to the lathing or support wall of plaster or wall board from a wall

One standard dye marker thrown into
the sea

A piece of masonite painted allowed
to dry
Sanded for a certain time elapsure w
ith a standard flat finishing sander
And secured to the wall or floor

One sheet of transparent plastic secured to the floor or wall

A rectangular canvass and stretcher support with a rectangular removal from one of the four corners sprayed with paint for a time elapsure

Common steel nails driven into the floor at points designated at time of installation

An amount of paint poured directly upon the floor and allowed to dry

A series of stakes set in the ground
at regular intervals to form a rectangle
Twine strung from stake to stake to
demark a grid

Specific Statements

Two sheets of standard 8-1/2" X 11" typing paper bonded at equal distance from on either side of the white line of the Los Angeles Freeway
The utilization of a broken double or otherwise line in no way alters the intent

Three minutes of forty pound pressure spray of white highway paint upon a well tended lawn

The lawn is allowed to grow and not tended until the grass is free of all vestiges of white highway paint

One sheet of clear plexiglass of arbitrary size and thickness secured at the four corners and exact center by screws to the floor

One square limestone slab of arbitrary thickness

One sheet of brown wrapping paper bonded even with the edges to the top surface of the limestone

One hole in the ground approximately
one foot by one foot by one foot
One gallon water base white paint po
ured into this hole

Four strips of linoleum of arbitrary width cemented to the floor edge to edge with the fourth strip one width shorter than the preceding three

One aerosol can of enamel sprayed to
conclusion directly upon the floor

One standard interior grade sheet four foot by eight foot by three quarter inch plywood secured at the four corners and exact center by screws to the wall

One quart exterior green enamel thro
wn on a brick wall

A sheet of brown paper of arbitrary width and length of twice that width with a removal of the same proportions glued to the floor

A 2" wide 1" deep trench cut across
a standard one car driveway

One 106" X 16" slab of "Dow HD
300" styrofoam sunk flush with the
ground